
MODEL HPH1-050-SS-R1

HOT WATER HEAT PUMP






Feature:

- 100% stainless steel chassis
- High Efficiency Scroll Compressor
- Save up 70% of the energy Comparision between Electric Heater and Hot water heat pump
- Flow Rate up to 450 Liter per hour @Temp Diff 30°C
- Controller Built in Digital Thermostat
- Each unit is leak-teated, pre-charged and test run in all operating models
- All model are available with standard new environmentally friendly R-134a

Applications:

- Hotels
- Resorts
- Condominiums
- Apartments
- University
- Hospital





PHYSICAL DATA & ELECTRICAL DATA

MODEL			HPH1-050-SS-R1
NOMINAL CAPACITY		BTUH	55,000
RATED AIR FLOW AT HIGH SPEED		CFM	2,000
WATER IN		°C	30
WATER OUT		°C	60
FLOW RATE		GPM	2.03
		L / Minute	7.68
CONDENSOR COIL		TYPE	Plate Heat Exchanger
COMPRESSOR		TYPE	Scroll
	POWER INPUT	WATT	5180
	RATED CURRENT	AMP.	8.8
	PROTECTION DEVICES	TYPE	Internal Overload Protection
	POWER SUPPLY	VOLT / PHASE / Hz	380/3/50
FAN		TYPE	Centrifugal
	MOTOR	WATT	193
	RATED CURRENT	AMP	0.89
	POWER SUPPLY	VOLT / PHASE / Hz	220/1/50
EVAPORATOR COIL		TYPE	3/8 " Innergroove Copper Tube with Aluminium Louver Fin
REFRIGERANT		TYPE	R - 134a (HOLDING CHARGE)
CONTROL		TYPE	Control Digital Temp
EXPANSION DEVICE		TYPE	Expansion Valve
AIR FILTER		TYPE	Aluminum
CONNECTION	CONNECTION	TYPE	Sweat Type
	SUCTION LINE	INCH (OD)	3/4
	LIQUID LINE	INCH (OD)	1/2
DIMENSION	WIDTH	MM.	1120
	HEIGHT	MM.	650
	DEPTH	MM.	900
WEIGHT		KGS.	135

Specifications are subjected to change without notice for future improvement.





















